



Shown with optional accessories.

HOOD COLORS	
FACTORY-INSTALLED PACKAGES	N/A
BED OPTIONS	Poly
ENGINE	277cc Carbureted KOHLER Command Pro®
SPEED	22 mph
<b>ELECTRONIC POWER STEERING</b>	N/A
HAUL	400 lbs
тоw	1,100 lbs



## L3 (4x2)



## THE BEST COMBINATION OF DURATION AND COVERAGE IN THE INDUSTRY

We build UTVs at American LandMaster with the intention of our customers never needing to use a warranty, but we know things can happen. The Easy Life Warranty from American LandMaster is a 12-month bumper-to-bumper limited warranty. Does limited sound confusing? It isn't. As long as you care for your machine like you should, don't wreck it, or crush it, we're going to cover it. Except for tires, brake pads, batteries, damage, neglect. That's the limit. Visit Landmaster.com to learn more.

POWER	9.5HP   277cc Commercial Engine Kohler 4-Stroke OHV single cylinder with low oil shutdown
SEATING CAPACITY	2 Person
SPEED	22 mph
FUEL CONSUMPTION	32 mpg*
RANGE	Up to 100 miles*
STARTING	12V keyed ignition / recoil backup
BATTERY	12V / 315 cca utility class
SPARK PLUG	NGK BKR5E
FUEL CAPACITY	5.0 gal
ALTERNATOR	10 amp
TRANSMISSION	CVT automatic
TRANSAXLE	H-12 Schafer / DANA gearbox
DIFFERENTIAL	Limited Slip Differential
DRIVE	2 wheel drive
FRONT SUSPENSION	Double A-arms, adjustable shocks with up to 3" travel
REAR SUSPENSION	Articulated rear swing arm, featuring quad adjustable shocks with up to 3" travel
BRAKE SYSTEM	6.25" dual rear hydraulic drum with hand operated parking brake
TIRES	25 x 8 - 12 (front) 25 x 10 - 12 (rear)
DIMENSIONS	95" L x 50" W x 77" H. (110" L With Poly Bed)**
WHEEL BASE	73"
TURNING RADIUS	9' inside radius
GVWR	1,700 lbs.
CURB WEIGHT	900 lbs.
BED MATERIALS	Structural foam "Poly Bed" with stake pockets
BED DIMENSIONS	35.25" L x 41.5" W x 11" D
BED CAPACITY	9 cu.ft. / 400 lbs.
TOWING CAPACITY	1,100 lbs.
TOTAL PAYLOAD	800 lbs.
WARRANTY	3 year engine / All other 1 year limited
ADDITIONAL FEATURES	3pt lap/shoulder belts for driver and passenger, twin 12V auxiliary outlets for accessories, 12V/18W LED headlights, polyurethane powder paint, 2" rear receiver hitch, dump bed, bench seating, welded steel frame. Fuel gauge located on fuel tank. In-dash, hour/volt meter standard.

<sup>\*</sup> Estimates. Actual top speeds, fuel consumptions and vehicle ranges may vary due to driving conditions, terrain, climate and other extenuating circumstances. 
\*\*Overall vehicle dimensions may vary with the addition of optional accessories