

I-SERIES MODEL SPECIFICATIONS



I-1100 SPECIFICATIONS

Size	Frame Sections	Number of Coulters*	Transport Height	Transport Width	Approx. Lbs. with harrows	H.P. Required*
12'	1	19	No wings	13'3"	7,400	120 - 140
16'	3- Flat fold	25	10'	10'	9,500	160 - 190
20'	3	33	11'2"	13'3"	12,200	200 - 240
24'	3	37	12'8"	13'3"	14,400	240 - 290
28'	3	45	13'	15'8"	17,400	280 - 340
31'	3	49	14'6"	15'8"	18,100	310 - 370
36'	3	57	14'2"	21'	21,900	360 - 430
41'	3	65	16'6"	21'	23,300	410 - 490
41'	5 Bi-fold	65	13'6"	18'9"	28,700	410 - 490
50'	5 Bi-fold	79	14'3"	19'	33,600	500 - 600+
60'	5 Bi-fold	97	15'8"	21'10"	39,200	600+

I-1200 SPECIFICATIONS

Size	Frame Sections	Number of Coulters*	Transport Height	Transport Width	Approx. Lbs. with harrows	H.P. Required*
12'	1	29	No wings	13'3"	8,400	120 - 140
16'	3- Flat fold	37	10'	10'	11,400	160 - 190
20'	3	49	11'2"	13'3"	13,400	200 - 240
24'	3	57	12'8"	13'3"	16,000	240 - 290
28'	3	69	13'	15'8"	19,200	280 - 340
31'	3	73	14'6"	15'8"	19,900	310 - 370
36'	3	85	14'2"	21'	24,300	360 - 430
41'	3	97	16'6"	21'	31,000	410 - 490
41'	5 Bi-fold	97	13'6"	19'	26,100	410 - 490
50'	5 Bi-fold	119	14'3"	19'	36,700	500 - 600+
60'	5 Bi-fold	145	15'8"	21'10"	43,000	600+

* Horsepower requirements vary by speed and operating depth. Transport dimensions include harrows.