

I-2100 SPECIFICATIONS

Size	Frame Sections	COIL-TECH II Number of Coulters*	Transport Height	Transport Width	Approx. Lbs. with harrows	H.P Required*	SwitchBlade 1,300lb Hyd. Shank Kits			
							15" Spacing		30" Spacing	
							# of Shanks	Fertilizer Coverage	# of Shanks	Fertilizer Coverage
12'	1	19	No wings	13'3"	8,000	140 - 170	9	11'3"	5	12'
16'	3 Flat Fold	25	10'	10'	11,400	190 - 220	11	13'9"	6	15'
20'	3	33	11'2"	13'3"	15,700	240 - 280	15	16'3"	8	17'6"
24'	3	37	12'8"	13'3"	16,200	290 - 340	17	21'3"	9	22'6"
28'	3	45	13'	15'8"	19,700	340 - 390	21	26'3"	11	27'6"
31'	3	49	14'6"	15'8"	20,500	370 - 430	23	28'9"	12	30'
36'	3	57	14'2"	21'	24,700	430 - 500	27	33'9"	14	35'
41'	3	65	16'6"	21'	26,600	490 - 570	31	38'9"	16	40'
41'	5 Bi-fold	65	13'6"	19"	31,900	490 - 570	31	38'9"	16	40'
50'	5 Bi-fold	79	14'3"	19'	37,500	600+	39	48'9"	19	47'6"
60'	5 Bi-Fold	97	15'8"	21'10"	44,100	600+	47	58'9"	23	57'6"

I-2200 SPECIFICATIONS

Size	Frame Sections	COIL-TECH II Number of Coulters*	Transport Height	Transport Width	Approx. Lbs. with harrows	H.P Required*	SwitchBlade 1,300lb Hyd. Shank Kits			
							15" Spacing		30" Spacing	
							# of Shanks	Fertilizer Coverage	# of Shanks	Fertilizer Coverage
12'	1	29	No wings	13'3"	10,200	140 - 170	-	-	-	-
16'	3	37	10'	10'	14,000	190 - 220	-	-	-	-
20'	3	49	11'2"	13'3"	17,000	240 - 280	15	16'3"	8	17'6"
24'	3	57	12'8"	13'3"	19,000	290 - 340	17	21'3"	9	22'6"
28'	3	69	13'	15'8"	23,700	340 - 390	21	26'3"	11	27'6"
31'	3	73	14'6"	15'8"	24,400	370 - 430	23	28'9"	12	30'
36'	3	85	14'2"	21'	30,000	430 - 500	27	33'9"	14	35'
41'	3	97	16'6"	21'	36,800	490 - 570	31	38'9"	16	40'
41'	5 Bi-fold	97	13'6"	18'9"	32,300	490 - 570	31	38'9"	16	40'
50'	5 Bi-fold	119	14'3"	19'	47,170	600+	39	48'9"	19	47'6"

* Horsepower requirements vary by speed and operating depth. Transport dimensions include harrows. Shank kits require an additional average of 3 horsepower per shank.

** 5 Section bi-fold frame